
CITY OF UNALASKA WESTWARD/CITY INTERTIE PROJECT #16-0011




| $\mathrm{DR}A$ | WING INDEX | | | |
|---|-------------------|----------|----------|-------|
| TITLE | DRAWING NUMBER | SHEET | REVISION | NOTES |
| SITE PLAN | E1.01 | 2 | 0 | |
| WESTWARD FACILITY SITE PLAN — UNDERGROUND UTILITIES WITH NEW ELEC. ONLY | E1.02 | 3 | 0 | |
| VESTWARD FACILITY SITE PLAN — UNDERGROUND ELECTRIC POWER ONLY — NEW | E1.03 | 4 | 0 | |
| VESTWARD FACILITY SITE PLAN - UNDERGROUND UTILITIES WITH NEW/EXISTING FIBER | E1.04 | 5 | 0 | |
| VESTWARD FACILITY SITE PLAN — UNDERGROUND FIBER ONLY — NEW CAPTAIN'S BAY ROAD — SITE PLAN | E1.05 E1.06 | 6 7 | 0 | |
| CAPTAIN'S BAY ROAD - SITE PLAN | E1.07 | 8 | 0 | |
| CAPTAIN'S BAY ROAD — SITE PLAN | E1.08 | 9 | 0 | |
| CAPTAIN'S BAY ROAD INTERSECTION — SITE PLAN | E1.09 | 10 | 0 | |
| ETAIL DRAWINGS | E1.10 | 11 | 0 | |
| AULT LOCATIONS | E1.11 | 12 | 0 | |
| AULT LOCATIONS | E1.12 | 13 | 0 | |
| AULT LOCATIONS | E1.13 | 14 | 0 | |
| NACLE LINE DIACDAM EVICTING | F2 01 | 15 | 0 | |
| SINGLE LINE DIAGRAM — EXISTING SINGLE LINE DIAGRAM — EXISTING | E2.01 E2.02 | 15 16 | 0 | |
| SINGLE LINE DIAGRAM — EXISTING SINGLE LINE DIAGRAM — PROPOSED | E2.02 | 17 | 0 | |
| SINGLE LINE DIAGRAM — PROPOSED | E2.04 | 18 | 0 | |
| COMMUNICATION NETWORK DIAGRAM AND DETAILS | E2.05 | 19 | 0 | |
| COMMUNICATION VAULT DETAILS | E2.06 | 20 | 0 | |
| VESTWARD UTILITY COMMUNICATIONS SINGLE LINE DIAGRAM | E2.07 | 21 | 0 | |
| VESTWARD UTILITY THREE LINE DIAGRAM C-9VCR1 | E2.08 | 22 | 0 | |
| WESTWARD UTILITY FIBEROPTIC LINK FV-1 & FV-2 | E2.09 | 23 | 0 | |
| WESTWARD UTILITY AGNES BEACH (AB-1) ENCLOSURE OVERVIEW | E2.10 | 24 | 0 | |
| DONICT DUCTION LINUTO | F7 ^4 | 0.5 | | |
| CONSTRUCTION UNITS | E3.01 | 25 | 0 | |
| CONSTRUCTION UNITS CONSTRUCTION UNITS | E3.02 E3.03 | 26 27 | 0 | |
| CONSTRUCTION ONLY | L3.03 | 21 | U | |
| MVA TRANSFORMER | EQ1.01 | 28 | 0 | |
| 88 KV 630 AMP PADMOUNT STYLE SOLID DIELECTRIC RECLOSER | EQ1.02 | 29 | 0 | |
| COOPER FOUR WAY SWITCH | EQ1.03 | 30 | 0 | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |



SHEET 1 OF 30

T0.01

| PROJ DESI | PROJECT: WESTWARD/CITY INTERTIE PROJECT DESIGNER/PROJECT ENGINEER: WILLIAM FARRELL/EARL GEORGE - EPS JOB #: 16-0011 | | | | | | |
|--------------|---|----------------|------------------|---|--|--|--|
| NO. | DESIGN/CONSTRUCTION/ASBUILT REVISION | DWN BY/DATE | REVIEWED BY/DATE | | | | |
| 0 | ISSUED FOR BID | DRK/03-30-2017 | WBF/03-30-2017 | 1 | | | |
| | | | | - | | | |
| | | | | 1 | | | |
| | | | | - | | | |
| | | | | - | | | |






| | | | TEL: (907) 522-1953 CERTIFICATE |
|-----|-------------------|---|---------------------------------|
| NO. | DRAWING NO./SHEET | REFERENCE DRAWING/DETAIL/PLAN/SECTION DESCRIPTION | DRAWING NAME: CITY OF UNALASKA |
| | | | WESTWARD/CITY INTERTIE |
| | | | TITLE AND DRAWING INDEX |
| | | | |

REF DWG(S):

DRAWING NO.:



- 5) CONTRACTOR IS REQUIRED TO LOCATE ALL EXISTING 12kV FEEDERS PRIOR TO DIGGING AND DEMOLITION TO IDENTIFY FINAL ROUTES AND DEPTHS AS REQUIRED. NOTIFY CITY AND WESTWARD PRIOR TO CONSTRUCTION AS WESTWARD WILL NEED TO GO ON THEIR OWN POWER AND PROVIDE POWER TO OTHER DOWNSTREAM CUSTOMERS; THIS WILL ALLOW FOR DE-ENERGIZATION AND ISOLATION OF THE 12kV FEEDER FOR DEMOLITION.
- 6) ALLOWANCE FOR BURIAL DEPTHS LESS THAN 48" WILL ONLY BE ALLOWED PER APPROVAL BY THE PROJECT ENGINEER ON A CASE—BY—CASE BASIS.
- 7) INSTALL NEW 35kV POWER AND FIBER OPTIC CONDUITS IN THE SAME LINEAR ROUTE AS THE EXISTING 12 KV FEEDER. EXISTING CONDUIT DEPTHS VARY GREATLY. NEW CONDUIT SHOULD BE INSTALLED AT DEPTHS DESCRIBED IN TRENCH DETAIL ON SHEET E3.02.
- 8) PROVIDE SLACK LOOP FOR 35kV (40') AND FIBER (50') IN ALL NEW VAULTS PER STAKING SHEETS.
- 9) CONTRACTOR IS REQUIRED TO HAVE A PROFESSIONALLY LICENSED SURVEYOR ON HAND TO ENSURE NO INSTALLATION OF UTILITIES FALLS OUTSIDE OF THE RIGHT OF WAY.
- 10) LOCATIONS OF UTILITIES ARE APPROXIMATE AND NOT REPRESENTATIVE OF ACTUAL FINAL LOCATION. PRIVATE UTILITY AND PUBLIC UTILITY LOCATES MUST BE COMPLETED PRIOR TO CONSTRUCTION, INCLUDING AREA AROUND TANK FARM.
- 11) THE DISTINCTION BETWEEN "REMOVE" AND "REMOVE AND SALVAGE" ON THESE DRAWINGS IS AS FOLLOWS:

 "REMOVE" = DETACH ITEM FROM EXISTING CONSTRUCTION AND LEGALLY DISPOSE OF THEM OFF-SITE

 UNLESS INDICATED TO BE REMOVED AND SALVAGED OR REMOVED AND REINSTALLED.
 - "REMOVE AND SALVAGE" = CAREFULLY DETACH FROM EXISTING CONSTRUCTION, IN A MANNER TO PREVENT DAMAGE. AND DELIVER TO OWNER READY FOR REUSE.
- 12) VAULT LOCATIONS ARE PROPOSED ONLY. CONTRACTOR SHALL STAKE RIGHT OF WAY BOUNDARY AND THEN COORDINATE VAULT LOCATIONS WITH UTILITY. LOCATIONS SHALL BE WITHIN THE LEVEL SHOULDER INSIDE OF RIGHT OF WAY AS CLOSE TO EMBANKMENT AS PRACTICAL.
- 13) FOR INFORMATION AND COORDINATES DONE ON THE 15 TEST PITS LOCATED ON THESE DRAWINGS REFER TO THE DECEMBER 16TH, 2016 REPORT "CAPTAINS BAY ELECTRICAL INTERTIE—TEST PITS" DONE BY ROBERT LUND, P.E. CITY OF UNALASKA DPW.

NEW VAULT LOCATIONS (ROAD SIDE FRONT EDGE OF VAULT)

| VAULT # | NORTHING | EASTING |
|---------|--------------|--------------|
| C-1 | FIELD STAKE | FIELD STAKE |
| C-2 | 1,181,779.63 | 5,315,498.81 |
| C-3 | 1,180,832.07 | 5,315,289.81 |
| C-4 | 1,180,090.67 | 5,315,293.71 |
| C-5 | 1,179,194.88 | 5,315,464.24 |
| C-6 | 1,178,480.35 | 5,315,349.49 |
| C-7 | 1,178,074.08 | 5,315,300.31 |
| C-8 | 1,177,681.45 | 5,315,016.27 |

CULVERT INVERT ELEVATIONS

| CULVERT # (STA.) | WEST INV. EL. | EAST INV. EL. | ROAD CL. EL. | CULV. DIAMETER |
|------------------|---------------|---------------|--------------|----------------|
| 12+35 | 12.4' | 13.2' | 19.72' | 24" |
| 23+03 | 4.3' | 7.5' | 12.21' | 12" |
| 27+31 | 5.8' | 8.2' | 11.84' | 18" |
| 30+92 | 5.9' | 8.0' | 12.59' | 18" |
| 33+69 | 7.3' | 9.2' | 11.98' | 18" |
| 37+21 | ? | 8.7' | 11.92' | 12" |
| 38+95 | 6.6' | ? | 11.11' | 18" |
| 42+53 | ? | 7.0' | 10.38' | 18" |
| 46+06 | 6.1' | ? | 11.58' | 12" |
| 47+03 | 5.2' | 7.3' | 11.28' | 12" |
| 50+15 | ? | 9.0' | 11.44' | 12" |
| 55+55 | ? | ? | 11.78' | ?" |
| 57+03 | 3.7' | 6.8' | 11.86' | 18" |
| 58+89 | 5.5' | ? | 11.49' | 12" |
| 62+11 | 3 7' | 8 7' | 13 34' | 36" |



Consulting Engineers

EL: (907) 522–1953

SINGLE (907) 522–1953

EL: (907) 522–1953

SINGLE (907) 522–1953

SINGLE (907) 522–1953

SINGLE (907) 522–1953

500 0 500 1000 FEET



| PROJ | JECT: WESTWARD 35 kV INTERTIE DESIGN-BUILD | | | |
|-------|---|--------------|--------------------------|--------------------------|
| DESIG | GNER/PROJECT ENGINEER: WILLIAM FARRELL/EARL GEORGE - EP | S | w.o. #: <u>1</u> | 6-0011 |
| NO. | DESIGN/CONSTRUCTION/ASBUILT REVISION | DWN BY/DATE | REVIEWED (MGR/SUPV)/DATE | APPROVED (DIRECTOR)/DATE |
| 0 | ISSUED FOR BID | DRK/04-10-17 | WBF/04-10-2017 | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |







DUTCH HARBOR WESTWARD/CITY INTERTIE SITE PLAN


E1.01


G(S): 16-0011_captain_bay_road_line_extension.dwg


2 0 30















































| NO. | DRAWING NO./SHEET | REFERENCE DRAWING/DETAIL/PLAN/SECTION DESCRIPTION | DRAWING NA |
|-----|-------------------|---|-------------|
| 1 | E2.01/1 | SINGLE LINE DIAGRAM — EXISTING | |
| | | | |
| | | | |
| | | | |
| | | | REF DWG(S): |
| | | | |


CITY OF UNALASKA
WESTWARD/CITY INTERTIE


Consulting Engineers


| | | | OIAII | | | |
|--------|-------|------|-------|------------|--------|----|
| WE | STWAR | 2D/C | ITY | INTE | ERTIE | |
| SINGLE | LINE | DIA | GRAM | 1 – | EXISTI | NG |
| | | | | | | |

| | | e2.02.dwg |
|---|----------------------|--------------------|
| | REF DWG(S): | |
| 1 | | |
| | DRAWING NO.: $E2.02$ | SHEET 16 OF 30 |











FIBER VAULT AND DOME PLAN DETAIL (N.T.S.)
(NOT ALL VARIATIONS SHOWN. SEE BOM FOR SPECIFIC DETAILS)



FIBER VAULT AND DOME ELEVATION DETAIL (N.T.S.)
(NOT ALL VARIATIONS SHOWN. SEE BOM FOR SPECIFIC DETAILS)



FIBEROPTIC CABLE PATCH PANEL ELEVATION DETAIL (N.T.S)

| NUMBER | UNIT | QTY. | DESCRIPTION | LOCATION | MFGR./CATALOG NO. | NOTE |
|--------|------|------|-------------|----------------|---|--|
| 1 | EA | 2 | GLC-1 | FV-0,FV-3 | PREFORMED LINE PRODUCTS/COYGLC-C4-000 | LARGE BASE W/ COVER AND PLUG |
| 2 | EA | 2 | GLC-2 | FV-1,FV-2 | PREFORMED LINE PRODUCTS/COYGLC-C4-001 | LARGE BASE W/ COVER AND NO PLUG |
| 3 | EA | 1 | GLC-3 | FV-1 | PREFORMED LINE PRODUCTS/COYGLC-F7-000 | 28" CROSS-CONNECT ORGANIZER |
| 4 | EA | 1 | GLC-4 | FV-2 | PREFORMED LINE PRODUCTS/COYGLC-F3-000 | 17" CROSS-CONNECT ORGANIZER |
| 5 | EA | 2 | GLC-5 | FV-1,FV-2 | PREFORMED LINE PRODUCTS/COYGLC-S5-000 | GROUNDING SPACER |
| 6 | EA | 12 | GLC-6 | AB-1,FV-1,FV-2 | PREFORMED LINE PRODUCTS/P12LC3** OR EQUAL | SINGLE MODE (OS1/OS2) FACTORY POLISHED LC 12-FIBER PIGTAIL |
| 7 | EA | 3 | TRAY-1 | FV-1,FV-2 | PREFORMED LINE PRODUCTS/80809958 | 24CT DEEP PROFILE SPLICE TRAY |
| 8 | EA | 1 | TRAY-2 | FV-1 | PREFORMED LINE PRODUCTS/80808945 | 40CT DEEP PROFILE SPLICE TRAY |
| 9 | EA | 12 | FAP-1 | FV-1,FV-2 | PREFORMED LINE PRODUCTS/12SMLC | 12 LC/UPC ADAPTER MODULE |
| 10 | EA | 1 | ENCL-1 | AB-1 | PENTAIR/PTHS242436X | ENCLOSURE STAINLESS |
| 11 | EA | 1 | ENCL-2 | AB-1 | PENTAIR/PTR24T* INCLUDED IN (ENCL-1) | RAIL KIT |
| 12 | EA | 1 | ENCL-3 | AB-1 | PENTAIR/CP2020 | BACK PLATE |
| 13 | EA | 2 | TERM-1 | AB-1 | PANDUIT/FRME1U | 3 FAP OPTICOM RACK MOUNT FIBER ENCLOSURE**ACCESSORIES |
| 14 | EA | 4 | TERM-2 | AB-1 | PANDUIT/FAP6WBUDLCZ | FIBER ADAPTER PLATES 6 LC/DUPLEX |
| | | | | | | |
| | | | | | | |

to fiber backbone shall be through the means of fusion splice to manufactured, factory polished type LC pigtials. No mechanical splices or terminations allowed.

**Exception — Allowed for temproary connection for cable acceptace testing and Verification

**Contractor is responsible for providing fusion splicing and testing equipment as well as any labor or miscellaneous components required to carry out the required tasks. These may include but are not limited to: precision allower atrippers applied traver applied to the providing fusion splices are allower.

tasks. These may include but are not limited to: precision cleaver, strippers, splice trays, splints, heat shrink, tie wraps, bushings, seals, hand tools, cleaners, safety equipment and consumables.

**Contractor is responsible for all conduit, raceway, patch cables and accessories required to complete system as outlined in the scope of work and project drawings. All pull points, termination points and enclosures shall be such that they do not exceed the fiber cable manufacturer installation requirments or permanent bending radius requirments after installation. No Condulets allowed in Fiber raceway path, No exceptions.

**Bid Alternate #1 — Alternate bid item is for the purchase, mobalization, installation and testing of approx. 7,000 feet of non conductive 18/pr (36 count) OS1/OS2

fiber—optic cable between FV—1 and AB—1. All conduit, raceway, enclosures, vaults, pedestals and components as shown on the drawings to facilitate this install will be installed regardless of the acceptance of the alternate bid item.

NOTES:

INSTALL 50' OF CABLE SLACK IN EACH VAULT ON THE CABLE RACKS FOR BOTH LS-9 AND WESTWARD CABLES. EACH CABLE LOOP MUST REMAIN ON THE CABLE RACKS OF EVERY WALL OF THE VAULT CREATING A LOOP RADIUS OF NOT LESS THAN 12". 50' OF SLACK LOOP IS TO FACILITATE MAINTENANCE FOR ALL IN COMING AND OUT GOING FIBER FEEDS.
 SLACK LOOPS IN VAULT NOT SHOWN FOR CLARITY
 SEE REFERENCE 6 AND STAKING SHEETS FOR CONDUIT PLANS FOR EACH VAULT.



PROJECT: WESTWARD/CITY INTERTIE PROJECT

DESIGNER/PROJECT ENGINEER: WILLIAM FARRELL/EARL GEORGE - EPS

JOB #: 16-0011

NO. DESIGN/CONSTRUCTION/ASBUILT REVISION

DWN BY/DATE


REVIEWED BY/DATE

DRK/03-30-2017

WBF/03-30-2017

DRK/03-30-2017







| | | | TEL: (907) 522–1953 | CERTIFICATE OF AU |
|--------|---|------------------------------------|---------------------|-------------------|
| /SHEET | REFERENCE DRAWING/DETAIL/PLAN/SECTION DESCRIPTION | CITY OF ESTWARD/O IUNICATION | | ERTIE |
| | | | | |

DRAWING NO.:

| | | COMMITTON | VIICLI | | |
|---|-------------|-----------|--------|----|--------|
| | | | | | |
| | | | | e2 | .06.dw |
| | REF DWG(S): | | | | |
| - | | | | | |

E2.06 SHEET 20 OF 30





NOTES:

- INSTALL 3/C #14 XHHW-2 FOR RECLOSER CONTROL POWER. SEE STAKING SHEETS FOR CONDUIT SCHEDULE
 DIN RAIL MOUNTED BREAKER(S) 1 MAIN AND 2 EACH LOAD MOUNTED IN A STAINLESS ENCLOSURE, WITH TERMINALS FOR LOAD SIDE OF BREAKER AS WELL AS GROUND CONNECTION AND NEUTRAL CONNECTIONS.
 VERIFY TERMINATION POINTS WITH THE RECLOSER AS-BUILT DRAWINGS TO BE PROVIDED BY THE OWNER
 RELAY PROGRAMMING AND COMMISSIONING BY OTHERS.
 INSTALL TERMINATION BLOCK INSIDE TRANSFORMER W/PROVISIONS FOR 4 EACH 120 LOAD TERMINALS FROM EACH CIRCUIT, 4 NEUTRAL TERMINALS AND 8 GROUND TERMINALS PER CIRCUIT.


| ELE STATE | Clectric Power Systems Inc. | | | | |
|---------------------|---|--|--|--|--|
| TEL: (907) 522–1953 | Consulting Engineers 3305 ARCTIC BLVD, STE 201, ANCHORAGE, AK 99503 CERTIFICATE OF AUTHORIZATION: AECC 738 | | | | |

E2.08

e2.08.dwg

SHEET 22 OF 30

| PROJ DESIG | PROJECT: WESTWARD/CITY INTERTIE PROJECT DESIGNER/PROJECT ENGINEER: WILLIAM FARRELL/EARL GEORGE - EPS JOB #: 16-0011 | | | | | | | |
|---------------|--|----------------|------------------|--|--|--|--|--|
| NO. | DESIGN/CONSTRUCTION/ASBUILT REVISION | DWN BY/DATE | REVIEWED BY/DATE | | | | | |
| 0 | ISSUED FOR BID | DRK/03-30-2017 | WBF/03-30-2017 | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |





| The sole | lectric Power Systems |
|----------|---|
| ePs : | inc. Consulting Engineers |
| SYSTEMS | TEL: (907) 522-1953 FAX: (907) 522-1182 WEB: WWW.EPSINC.COM |


NO. DRAWING NO.,


|)./SHEET | REFERENCE DRAWING/DETAIL/PLAN/SECTION DESCRIPTION | CITY OF UIWESTWARD/CIT | |
|----------|---|------------------------|---------|
| | | THREE LINE | DIAGRAM |
| | | C-9VC | CR1 |
| | | REF DWG(S): | |

DRAWING NO.:











NOTES:

- 1. SPECIFY ELBOW MATERIAL, DIAMETER, ANGLE, AND
 - "d" IS THE NOMINAL PIPE DIAMETER
- 2. BEND RADIUS TO BE DESIGNATED AS FOLLOWS:
 - LS LONG SWEEP 36" RADIUS FOR 2" 48" RADIUS FOR 4"
 - 60" RADIUS FOR 6" SS - SHORT SWEEP - 24" RADIUS FOR 2"
 - 36" RADIUS FOR 4" 48" RADIUS FOR 6"
 - FOR EXAMPLE, RSC290SS IS RIGID STEEL 2 INCH 90 DEGREE ELBOW WITH A 24 INCH BEND RADIUS.
- 3. UNIT INCLUDES INSTALLATION OF ANY BUSHINGS NECESSARY TO ATTACH TO ADJACENT CONDUIT.

CONDUIT ELBOW

(MATERIAL, DIAMETER, ANGLE, RADIUS) FBRdar. PVCdar, RSCdar







MISC. ACCESSORIES UNDERGROUND

MISC. ACCESSORIES UNDERGROUND


CONVERTED FROM OLDCASTLE PRECAST DRAWING "WA_AUB_6X6X3_ELECTRICALVAULT774LA_13074"








UM6-39 Uhf JACKETED CABLE GROUNDING KITS





| RUS | UTILITY | VAULT | MODEL | 4484-LA | OR | EQUIVALENT |
|-----|---------|-------|-------|---------|----|------------|
| | | | | | | |

1-1/2" DIA. GROUND

ROD KNOCKOUT, (2)

| | 1 | *Utility Vault Model 4484—LA or Equiv. |
|----|----------|--|
| | 1 | *Utility Vault Lid —AASHTO H—20/HS—20 Loading |
| ai | 4 | Rod, Ground, Galvanized Steel, 3/4" x 8' |
| aj | 4 | Clamp, Ground Rod |
| cj | As Req'd | Ground Wire, #4/0 BaCuStr |
| | 8 | Stanchion, Underground Devices CR36—B or Equiv |
| | 16 | Cable Rack, Underground Devices RA08 or Equiv |


ITEM QTY MATERIAL


GALVANIZED PULLING

IRON (2) EACH END,

(2) ENDS

each wall. 3. Seal all removed knock outs with 4. Coordinate actual dimensions of lid with owner furnished materials. CONCRETE VAULT





SECTION AA

| RUS | | |
|------|----------|--|
| ITEM | QTY | MATERIAL |
| | 1 | *Utility Vault Model 4484—LA or Equiv. |
| | 1 | *Utility Vault Lid —AASHTO H—20/HS—20 Loading |
| ai | 4 | Rod, Ground, Galvanized Steel, 3/4" x 8' |
| aj | 4 | Clamp, Ground Rod |
| Ċj. | As Req'd | Ground Wire, #4/0 BaCuStr |
| | 8 | Stanchion, Underground Devices CR36—B or Equiv |
| | 16 | Cable Rack, Underground Devices RA08 or Equiv |
| | | |


NOTES:

1. Install 4/0 bare copper ground stranded wire loop ground ring below floor of vault with 18" min. of cover. Terminate on ground rods

2. Install one complete loop of conductor in each vault attached to each wall.

3. Seal all removed knock outs with

CONCRETE VAULT



NOTES:

DRAWING NO.:

1) COMPLETE VAULT INSTALLATION INCLUDES INSTALLATION OF GROUND RODS AND GROUND WIRE LOOP IN BOTTOM OF VAULT.

2) PROVIDE A MINIMUM OF 24" BEDDING MATERIAL UNDER AND AROUND VAULT, COMPACTED TO 95% MAXIMUM PROCTOR


3) ALL BEDDING MATERIAL SHALL MEET THE REQUIREMENTS FOR E-1 AS SPECIFIED IN TABLE 703 IN THE ALASKA DEPARTMENT OF TRANSPORTATION AND PUBLIC FACILITIES STANDARD SPECIFICATION FOR HIGHWAY CONSTRUCTION, 2004 EDITION. 4) ALL CONDUIT ENTRY POINTS TO BE ADEQUATELY SEALED AFTER INSTALLATION AND PRIOR TO BACKFILLING.

5) ON EACH WALL INSTALL (2) 36" STANCHIONS WITH (2) CABLE RACKS PER STANCHION. USE (2) CABLE TIES TO SECURE EACH CABLE TO THE ARM PER MANUFACTURER'S RECOMMENDATIONS.

CONCRETE VAULT

| PROJ | PROJECT: WESTWARD/CITY INTERTIE PROJECT | | | | | | | | |
|---|---|----------------|------------------|--|--|--|--|--|--|
| DESIGNER/PROJECT ENGINEER: WILLIAM FARRELL/EARL GEORGE - EPS JOB Ø: 16-0011 | | | | | | | | | |
| NO. | DESIGN/CONSTRUCTION/ASBUILT REVISION | DWN BY/DATE | REVIEWED BY/DATE | | | | | | |
| 0 | ISSUED FOR BID | DRK/03-30-2017 | WBF/03-30-2017 | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |

MISC. ACCESSORIES UNDERGROUND





1. Install 4/0 bare copper ground

floor of vault with 18" min. of

cover. Terminate on ground rods.

Install one complete loop of


conductor in each vault attached to

774-LA DRAWING NAME: REFERENCE DRAWING/DETAIL/PLAN/SECTION DESCRIPTION NO. DRAWING NO./SHEET REF DWG(S):

WESTWARD SEAFOODS UNALASKA UTILITY INTERTIE DESIGN CONSTRUCTION UNITS

E3.01

SHEET 25 OF 30





4. ALL EXCAVATIONS SHALL BE IN COMPLIANCE WITH STATE AND


FEDERAL OSHA REQUIREMENTS FOR EXCAVATIONS.


THICKNESS AND KIND (AS REQUIRED),

- THIS UNIT INCLUDES THE COMPACTION OF BACKFILL TO MEET THE NOTES BELOW AND THE IMPORT AND EXPORT OF BACKFILL NECESSARY. THIS UNIT ALSO INCLUDES THE REPLACEMENT OF INSULATION AND/OR GEOTEXTILE FABRIC WITH A MATCHING
- 6. FOR OPEN CUT ROAD CROSSINGS THIS UNIT INCLUDES THE DEPTH 12. COMPACT BEDDING MATERIAL PRIOR TO PLACEMENT OF OF TRENCH NECESSARY TO MEET COMPACTION OF BACKFILL IN 12" LAYERS (MAX) TO ACHIEVE 90% COMPACTION. ALL BEDDING MATERIAL SHALL MEET THE REQUIREMENTS FOR E-1 AS SPECIFIED IN TABLE 703 IN THE ALASKA DEPARTMENT OF TRANSPORTATION AND PUBLIC FACILITIES STANDARD SPECIFICATION FOR HIGHWAY
- CONSTRUCTION, 2004 EDITION. . BOTTOM OF TRENCH SHALL BE FREE OF ANY SHARP ROCKS OR MATERIAL THAT MAY CAUSE DAMAGE TO CABLES. AT NO POINT SHALL THE CABLES SUSPEND OVER A HOLE OR GAP IN THE TRENCH. SUCH VOIDS SHALL BE FILLED WITH APPROPRIATE
- 9. WARNING TAPE SHALL BE PLACED 18 INCHES ABOVE THE INSTALLED CONDUIT.
- 10. INSTALL MAGNETIC CABLE LOCATOR DISCS AT THE BURIED ENDS OF ALL SPARE DUCTS. WARNING TAPE IS TO BE PLACED ABOVE THE INSTALLED CABLE 18 INCHES BELOW GRADE.
- 11. SURFACE MATERIAL SHALL MEET THE SAME GRADATION SPECIFICATION AS THE BEDDING MATERIAL.
- CONDUITS AND AGAIN AFTER CONDUIT ARE COVERED. COMPACT TO 90% MAXIMUM DENSITY. THE EXCAVATED MATERIALS SHALL BE SORTED TO REMOVE ROCKS IN EXCESS OF 12" DIAMETER FOR USE AS BACKFILL. THE OVERSIZED ROCKS SHALL BE DISPOSED OF SEPARATELY. UNCLASSIFIED MATERIAL CAN BE BACKFILLED IN A SINGLE LIFT PROVIDED THE THICKNESS DOES NOT EXCEED 12". COMPACT THE UNCLASSIFIED MATERIAL WITH A MINIMUM 10-TON VIBRATORY COMPACTOR TO MINIMIZE VOIDS. AFTER INSTALLATION OF SURFACING MATERIAL, COMPACT ENTIRE TRENCH WITH A MINIMUM 10-TON VIBRATORY COMPACTOR. COMPACT SO TRENCH IS CONSOLIDATED AND DOES NOT HAVE SOFT SPOTS OR RUTS FROM TIRE LOADS.









4. TAG PRIMARY AND SECONDARY CABLES PER GUIDE UTILITY SPECIFICATIONS.


5. SPECIFY PAD SEPARATELY. 6. INSTALL "DANGER" SIGN INSIDE TRANSFORMER AND "WARNING" SIGN ON OUTSIDE SURFACE OF ENCLOSURE. LABEL OUTSIDE OF TRANSFORMER PER GUIDE UTILITY

7. SPECIFY SIZE THEN SPECIFY SECONDARY VOLTAGE WITH LAST SUFFIX AS FOLLOWS: A -208Y/120

B -480Y/277 C - OTHER (SPECIFY ON DESIGN AND STAKING SHEETS) (i.e. UG17-2-75-B FOR 75 KVA AT 480Y/277 VOLTS SECONDARY)

THREE PHASE PAD-MOUNTED TRANSFORMER UG17-2 (LOOP FEED)/UG17-3 (RADIAL FEED)

SPECIFICATIONS.




Ground wire, #4 copper min. (as required)

SPECIFICATION NUMBER CODES: EXAMPLE: UM50-S-3 IS 3" STEEL CONDUIT -H-2 |-H-3 |-H-4 | -H-5 1-2" HDPE Conduit 1-3" HDPE Conduit 1-4" HDPE Conduit 1-5" HDPE Conduit 1-6" HDPE 1-2" P.V.C 1-3" P.V.C 1-4" P.V.C 1-5" P.V.C 1-6" P.V.C 1-2" Steel Conduit 1-3" Steel Conduit 1-4" Steel Conduit UM1-7C UM1-7NC 1-5" Steel Conduit


NO. DRAWING NO./SHEET

1-6" Steel Conduit



UM50-(H, P or S)-(DIAMETER)

| PE Conduit | | | | | 1 | |
|-------------|------|------|------|------|------|--|
| | | | | | | |
| | -P-2 | -P-3 | -P-4 | -P-5 | -P-6 | |
| .C. Conduit | 1 | | | | | NOTEC |
| .C. Conduit | | 1 | | | | NOTES: |
| .C. Conduit | | | 1 | | | 1) SPECIFY TRENCH UNIT SEPARATELY. |
| .C. Conduit | | | | 1 | | |
| .C. Conduit | | | | | 1 | 2) EACH UNIT CONSIST OF ONE LINEAR FOO OF CONDUIT. |
| | | | | | | OI CONDOIT. |
| | -S-2 | -S-3 | -S-4 | -S-5 | -S-6 | 3) HDPE AND PVC CONDUIT IS SCHEDULE 40 |
| al Canduit | 1 | | | | | UNLESS OTHERWISE SPECIFIED. |



2000

| | OF CONDUIT. |
|----|---|
| 3) | HDPE AND PVC CONDUIT UNLESS OTHERWISE SPECI |
| | |

| Uan | 1 | Transformer, pad mounted, single phase | | | | | |
|-----|----------------------------------|--|--|--|--|--|--|
| | | with one load break bushing per phase | | | | | |
| | and internal fuses (UG7 & UG17B) | | | | | | |
| Uhw | 2 | Signs, "DANGER" and "WARNING" | | | | | |
| Uhp | 1 | Elbow Termination | | | | | |
| | | Ground wire (See Note #3) | | | | | |
| | | Tape, as required | | | | | |
| | | | | | | | |
| | • | | | | | | |

Connectors, as required

bu | 2 | Connector, equipment ground

Jumpers, copper as required

MOUNTING ON PARKING STAND. TRAIN CABLES AS SHOWN. INSTALL WITH UNIT UM48-1 OR OTHER GROUNDING UNIT TO BE SPECIFIED SEPARATELY. 3. SPECIFY PAD OR SLEEVE UNIT SEPARATELY. 4. INSTALL "DANGER" SIGN ON TRANSFORMER AND "WARNING" SIGN ON ENCLOSURE. UG7 WITH -SS DESIGNATION IS FOR TRANSFORMER WITH 100% STAINLESS STEEL CONSTRUCTION.


<u> Power Systems</u>

3305 ARCTIC BLVD, STE 201, ANCHORAGE, AK 99503

EL: (907) 522–1953 CERTIFICATE OF AUTHORIZATION: AECC 738

| ow Termination und wire (See Note #3) | | SINGLE PHASE PAD MOUNTED TRANSFORMER (LOOP FEED) | | |
|--|-----------|--|------|-------------|
| e, as required | | | 2000 | UG7 UG7B |
| | 1 | | | |
| WESTW | ARD SEAFO | $\overline{\Omega}$ | | |

PROJECT: WESTWARD/CITY INTERTIE PROJECT DESIGNER/PROJECT ENGINEER: WILLIAM FARRELL/EARL GEORGE - EPS JOB ø: 16-0011 DESIGN/CONSTRUCTION/ASBUILT REVISION REVIEWED BY/DATE DWN BY/DATE O ISSUED FOR BID DRK/04-10-2017 WBF/04-10-2017





| Clect | ric Power Systems |
|---------|---|
| ePs co | inc. Onsulting Engineers |
| SYSTEMS | TEL: (907) 522-1953 FAX: (907) 522-1182 WEB: WWW.EPSINC.COM |

UM48-2


DRAWING NAME: REFERENCE DRAWING/DETAIL/PLAN/SECTION DESCRIPTION WESIWARD SEAFOODS UNALASKA UTILITY INTERTIE DESIGN CONSTRUCTION UNITS

e3.02.dwg REF DWG(S): DRAWING NO.: SHEET 26 OF 30E3.02






35KV VAULT 774-LA (INSIDE CABLE LAYOUT - FACING WALL "A")



35KV VAULT 774-LA (INSIDE CABLE LAYOUT - FACING WALL "B")



APPROVAL. DO NOT REUSE PLASTIC NATIVE OVERBURDEN MATERIAL

3. COMPACT IN 8" MAX LIFTS TO 95% MAX DENSITY PER ASTM D1557

PLAIN CONCRETE PER ACI 318 AND ADOT 501:

1. MIX DESIGN. ADOT 501 TYPE A-A - 7 SACK W/ 5-10% MICROSILICA FUME -

2. CLASSIFIED FILL TYPE A (3" MINUS) AGGREGATE OR SELECTED MATERIAL W/

EXCAVATION AND FILL PER ADOT 200/703:

BASE COURSE D−1

w/c 0.44 MAX - SLUMP 1-3" - AIR 5-8% - GRADATION AASHTO NO. 57 OR 67 - 28 DAY STRENGTH 5,000 PSI MIN.
2. SET ACCELERATING ADMIXTURES. CHLORIDE FREE - AASHTO M 194 - AS

NEEDED TO ALLOW TRAFFIC W/IN 7 DAYS OF POUR AT 80% OF STRENGTH

3. REINFORCEMENT. ASTM C 1116 BLENDED TYPE III SYNTHETIC FIBERS —

NOVOMESH 950 — 3 LBS PER CY OF CONC — MIXED IN TRUCK AT MAX SPEED FOR 5 MINUTES MIN.

4. CURE. USE WATER CURING METHOD. APPLY A PENETRATING SILANE BASED SEALER 28 DAYS AFTER POUR. MASTER KURE ER 50 IS ALLOWED DURING FINISHING IF USED IN ACCORDANCE WITH MFR. OR USE ONE STEP MEMBRANE CURING W/ ASTM C-309 CURE & SEAL W/ PENETRATING SILANE COMPONENT

5. TESTING. CONTRACTOR PROVIDE ENTRAINED AIR AND SLUMP TESTING IN FIELD. COLLECT CYLINDERS AND USE THIRD PARTY CERTIFIED LAB TO PROVIDE ACCEPTANCE TESTING FOR STRENGTH AT 7 AND 28 DAYS

6. CONTRACTION JOINTS. SCORED IN WALKWAYS. FORMED W/ FULL DEPTH 1/8"t SEPARATORS IN CURB. WALKWAYS USE TRANSVERSE CONTRACTION JOINTS EVERY 5' TYPE A AND 6' TYPE B WALKWAYS. CURBS USE TRANSVERSE CONTRACTION JOINTS EVERY 10' TYPE A AND 12' TYPE B WALKWAYS. ALIGN WALKWAY TO CURB CONTRACTION JOINTS

7. EXPANSION JOINTS. 1/2" BITUMINOUS EXPANSION JOINT FILLER MATERIAL PER ASTM D994 AND AASHTO M 33-48. IN BOTH WALKWAYS AND CURBS USE TRANSVERSE EXPANSION JOINTS EVERY 50', BEHIND PARALLEL CURBS, TO SEPARATE TRANSITIONS OR IRREGULARITIES, AND ABUTING FIXED STRUCTURES. ALIGN WALKWAY TO CURB EXPANSION JOINTS

8. FINISH. WOOD FLOAT AND FINE TRANSVERSE HAIR BROOM FINISH. UNSIGHTLY OR POORLY FORMED CONC OR CONC W/ 1/8" SURFACE DEFICIENCIES WILL BE REJECTED.

9. USE SPECIFIED MATERIALS OR APPROVED EQUAL

DRAWING NAME:

DRAWING NO.:

| CITY OF UNALASKA Department of Public Works | | WALKWAYS AND CURBS | | | | |
|--|---------|--------------------|--------|---------------|---------|--------------------------|
| DRAWN BY: | DATE: | APPROVED BY: | SCALE: | REVISION NO.: | PAGES.: | STANDARD DETAIL NO. 30-1 |
| RL | 3/15/17 | JD | N.T.S. | 2 | 2 of 2 | |

PROJECT: WESTWARD/CITY INTERTIE PROJECT
DESIGNER/PROJECT ENGINEER: WILLIAM FARRELL/EARL GEORGE - EPS

NO. DESIGN/CONSTRUCTION/ASBUILT REVISION


DWN BY/DATE

REVIEWED BY/DATE

DRK/03-30-2017

WBF/03-30-2017







e3.03.dwg


E3.03 SHEET 27 OF 30

STANDARD FEATURES: 1. L.V. BUSHINGS 2. H.V. BUSHINGS 3. TANK WITH WELDED-ON COVER 4. 1" FILL PROVISION 5. COOLING PANELS 6. HANDHOLE WITH TAMPERPROOF COVER 7. PRESSURE VACUUM GAUGE 8. LIFTING PROVISIONS 9. CORROSION RESISTANT NAMEPLATE AND CONNECTION DIAGRAM (NOT SHOWN) 10. LIQUID LEVEL GAUGE 11. DIAL TYPE THERMOMETER 12. DE-ENERGIZED TAPCHANGER 13. DRAIN VALVE AND SAMPLING DEVICE 14. NEMA GROUND PAD 15. SCHRADER VALVE 16. PRESSURE RELIEF VALVE 17. COMPARTMENT 18. STEEL DIVIDED 19. REMOVABLE FRONT SILL 20. JACK LUGS

KVA: 2000 HV: 34500Y/19919 LV: 12470/7200 TOTAL WEIGHT: 13604 LBS. FLUID VOLUME: 503 GALS.








1. DIMENSIONS ARE FOR REFERENCE ONLY AND ARE NOT FOR CONSTRUCTION. CONTRACTOR TO VERIFY FINAL DIMENSIONS OF OWNER FURNISHED EQUIPMENT PRIOR TO ORDERING VAULT AND LID.

| ELE ROY | <u>Power Systems</u> |
|---------------------|---|
| Sels 1 | Consulting Engineers |
| SYSTEMS | 3305 ARCTIC BLVD, STE 201, ANCHORAGE, AK 9950 |
| TEL: (907) 522-1953 | CERTIFICATE OF AUTHORIZATION: ÁECC 738 |

PROJECT: WESTWARD/CITY INTERTIE PROJECT
DESIGNER/PROJECT ENGINEER: WILLIAM FARRELL/EARL GEORGE - EPS REFERENCE DRAWING/DETAIL/PLAN/SECTION DESCRIPTION NO. DRAWING NO./SHEET WESTWARD SEAFOODS JOB Ø: 16-0011 UNALASKA UTILITY INTERTIE DESIGN Plectric Power Systems DESIGN/CONSTRUCTION/ASBUILT REVISION DWN BY/DATE REVIEWED BY/DATE 2 MVA TRANSFORMER DRK/03-30-2017 WBF/03-30-2017 0 ISSUED FOR BID - RAM 3.30-17 Consulting Engineers eq1.01.dwg William Brown-Farrell TEL: (907) 522-1953 FAX: (907) 522-1182 WEB: WWW.EPSINC.COM REF DWG(S): No. 14082 SYSTEMS DRAWING NO.: SHEET 28 OF 30EQ1.01



WESTWARD SEAFOODS DESIGNER/PROJECT ENGINEER: WILLIAM FARRELL/EARL GEORGE - EPS JOB ø: 16-0011 UNALASKA UTILITY INTERTIE DESIGN <u>Plectric Power Systems</u> DESIGN/CONSTRUCTION/ASBUILT REVISION DWN BY/DATE REVIEWED BY/DATE 38 kV 630 AMP PADMOUNT STYLE O ISSUED FOR BID DRK/04-10-2017 WBF/04-10-2017 SOLID DIELECTRIC RECLOSER RAN Consulting Engineers eq1.02.dwg William Brown-Farrell
No. 14082 TEL: (907) 522-1953 FAX: (907) 522-1182 REF DWG(S): SYSTEMS DRAWING NO.: WEB: WWW.EPSINC.COM SHEET 29 OF 30EQ1.02

